



基礎寸法表

項目	型式	φA	F1	F2	F3	総重量 kg
	KS-5	350	800	575	100	100
	KS-10	350	800	575	100	110
	KS-15	400	800	600	130	150
	KS-20	500	900	700	150	250
	KS-30	550	1,200	875	150	350
	KS-40	600	1,200	900	150	500
	KS-50	700	1,300	1,000	150	700
	KS-60	750	1,500	1,125	200	850
	KS-80	800	1,500	1,150	200	900
	KS-100	800	1,500	1,150	200	900

装置外観寸法表

項目	処理水量 m ³ /hr	φD1	φD2	H1	H2	L1	L2	φP1	φP2	圧力損失 mAg
KS-5	~5	205	105	1,600	1,350	180	85	40A	20A	6
KS-10	~12	205	130	1,750	1,500	180	85	40A	20A	7
KS-15	~17	255	155	1,850	1,600	200	100	50A	25A	6
KS-20	~20	350	200	2,150	1,820	270	135	65A	25A	6
KS-30	~30	400	200	2,450	2,070	300	155	80A	40A	6
KS-40	~40	450	200	2,650	2,240	325	180	80A	40A	6
KS-50	~50	550	250	3,000	2,570	370	220	100A	40A	6
KS-60	~60	600	250	3,200	2,950	400	245	100A	40A	6
KS-80	~80	650	300	3,500	2,950	420	260	150A	40A	6
KS-100	~100	650	300	3,550	3,020	420	260	150A	50A	7

(備考) 異砂部は消耗部材です。

NO.	ITEM	MAT'L	QTY	REMARKS
2011	July 25th	SCALE 1/1		SHEET 1/1
DWG.	ISLUI	TITLE		
ENG.		KS型異砂装置		
APP.		標準図		
DWG NO.	KISUI Water Treatment Design & Engineering, Inc.			